

Veco PC (Matting)

Manufacturing process	Tufted		ISO 2424
Gauge	1/8" Cutpile		
Fibre composition	100% PA6		
Primary backing	Non Woven		
Backing	PC		ISO 2424
Width	60*80 cm, 80*120 cm		
Total fibre weight of use surface	1225 gr/m ²		
Total weight	3790 gr/m ²	+/- 15%	ISO 8543
Pile height	6 mm		ISO 1766
Total height	9 mm	+15% / -10%	ISO 1765
Overall use class	Commercial 32, Areas with medium use		EN ISO 10874
Luxury class	LC5		EN 1307
Castor chair suitability	Yes, permanent use		EN 985
Stair suitability	Yes, permanent use		EN 1307
Colour fastness to light	≥ 5		ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4		ISO 105-X12
Colour fastness to water	≥ 4		ISO 105-E01
Colour fastness to soiling	≥ 3,5		EN 1269
Vertical resistance	Ω		ISO 10965
Horizontal resistance	Ω		ISO 10965
Slip resistance	DS (> 0,30)		EN 13893

Floorsymbols



Certificates

ISO 9001:2015-certified processes
ISO 14001:2015-certified processes

2022-01-10