

Tapiflex Excellence (19dB)

Datasheet

| Classification | Norm | Tarkett Value |
|--|----------------|--|
| Product type | EN ISO 11638 | Polyvinyl chloride floor coverings with foam layer |
| Commercial classification | ISO 10874 | 34 Very Heavy |
| Industrial classification | ISO 10874 | 42 General |
| Technical Characteristics | Norm | Tarkett Value |
| Total thickness | ISO 24346 | 3,25 mm |
| Wear layer thickness | ISO 24340 | 0,80 mm |
| Total weight | ISO 23997 | 3250 g/m ² |
| Surface treatment | | TEKTANIUM® |
| Installation method | | Glue-Down |
| Performance for CE Marking | Norm | Tarkett Value |
| Declaration of Performance # | EN 14041 | 0120-074-DoP-2024-01 |
| Reaction to fire | EN ISO 13501-1 | Bfl-s1 glued over any A2fl or A1fl substrate (concrete) and/or Cfl-s1 glued over any derivate wood substrate |
| Static Electrical Propensity | EN 1815 | Antistatic (≤ 2 kV) |
| Thermal resistance | EN ISO 10456 | 0,04 m ² •K/W |
| Slip resistance | EN 13893 | Class DS (μ ≥ 0,30) |
| Technical Performance | Norm | Tarkett Value |
| Residual indentation | EN ISO 24343-1 | Required value: ≤ 0,20 mm Average measured value: ca. 0,10 mm |
| Dimensional stability | EN ISO 23999 | ≤ 0.40 % Average measured value : ≤ 0.10 % |
| Impact sound reduction - ΔLw | EN ISO 717/2 | 19 dB |
| Reduction of in-room impact noise | NF S31-074 | Class A (≤ 65 dB) |
| Slip resistance | DIN 51130 | R10 |
| Furniture leg | EN ISO 16581 | No damage |
| Castor chair | EN ISO 4918 | No damage |
| Curl resultant to heat | EN ISO 23999 | ≤ 8 mm |
| Light fastness | EN ISO 105-B02 | ≥ 6 |
| Chemical resistance | EN ISO 26987 | Not affected |
| Underfloor heating | | Suitable (subfloor temperature maximum 27°C) |
| Sustainability performances | Norm | Tarkett Value |
| Recyclability through ReStart® | | Offcuts - Contact Tarkett for more information |
| Recycled content | | 25 % |
| Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3) | | 20,80 kg CO ₂ eq /m ² |
| Total VOC Emissions (after 28 days) | EN 16516 | Platinum (≤ 10 μg/m ³) |
| Dimensions and designs | | |
| Roll | | Roll 2 x 23 m |
| Number of designs available | | 93 |

Slip resistance : R10 only on wood designs (Serene oak, Long Modern Oak, Oak Tree, Scandinavian Oak, Allover wood)



The above information is subject to modification for the benefit of further improvement (01/08/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.