


# SAVAGE ABUNDANCE

## WILD LUXURY COLLECTION

<b>CONSTRUCTION</b> STRUCTURE STRUKTUR STRUCTUUR	Tufting 5/64" cut pile Tufté 5/64" cut pile Getuftet 5/64" cut pile Getuft 5/64" cut pile	<b>IMPACT NOISE RATING</b> ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNG GELUIDSISOLATIE	EN ISO 10140-3 27 dB ΔLw
<b>PILE MATERIAL</b> COMPOSITION DU VELOURS POLMATERIAAL POOLMATERIAAL	100% PA	<b>SOUND ABSORPTION</b> ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE	EN ISO 354 0,25 α W
<b>SECONDARY BACKING</b> DOSSIER RÜCKEN TAPIJTRUG	Twin back	<b>THERMAL RESISTANCE</b> RÉSISTANCE THERMIQUE WÄRMEDURCHLASSWIDERSTAND WARMTEDOORLAATWEERSTAND	ISO 8302 0,11 m <sup>3</sup> K/W
<b>PILE WEIGHT</b> POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 1.320 gr/m <sup>2</sup>	<b>FASTNESS TO LIGHT</b> SOLIDITÉ A LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID	ISO 105-B02 ≥ 5-6
<b>TOTAL WEIGHT</b> POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 2.200 gr/m <sup>2</sup>	<b>COLOUR FASTNESS TO WATER</b> SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID	EN ISO 105-E01 ≥ 4-5
<b>PILE THICKNESS</b> EPAISSEUR DU VELOURS POLDICKE POOLDIKTE	± 6 mm	<b>FIRE RESISTANCE</b> COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG	EN 13501-1 C <sub>FL</sub> -s1 if glued
<b>TOTAL THICKNESS</b> EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE	± 8,5 mm	<b>WIDTH</b> LARGEUR BREITE BREEDTE	EN ISO 3018 ca. 400, 500 cm
<b>TUFT DENSITY</b> NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 300.000/m <sup>2</sup>		
<b>PRODIS / GUT</b>	82D2CFDC		
<b>CLASSIFICATION</b> CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 23/32 - LC4		

**itc**



ITC CO BV  
Kanegemstraat 15, B-8700 Tielt  
itc-carpets.com

EN 14041 <b>CE</b>
18
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE00CV Textile Floor Covering EN1307 Notified Body 2401

myitc-carpets.com